

ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C ...). The first artifact folder for an artifact type receives the letter A, the second B, etc..
Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB

09915132BA

Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.

☐

CD(s) containing:

computer program listing

Doc Code: Computer

pages of specification

and/or sequence listing

and/or table

Doc Code: Artifact

content unspecified or combined

Doc Code: Artifact

☐

Artifact Type Code: P

☐

Artifact Type Code: S

☐

Artifact Type Code: U

☐

Stapled Set(s) Color Documents or B/W Photographs

Doc Code: Artifact Artifact Type Code: C

☐

Microfilm(s)

Doc Code: Artifact Artifact Type Code: F

☐

Video tape(s)

Doc Code: Artifact Artifact Type Code: V

☐

Model(s)

Doc Code: Artifact Artifact Type Code: M

☒

Bound Document(s)

Doc Code: Artifact Artifact Type Code: B

☐

Confidential Information Disclosure Statement or Other Documents
marked Proprietary, Trade Secrets, Subject to Protective Order,
Material Submitted under MPEP 724.02, etc.

Doc Code: Artifact Artifact Type Code X

☐

Other, description: _____

Doc Code: Artifact Artifact Type Code: Z

The
United
States
of
America



The Commissioner of
Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

J. Todd Pichini

Acting Commissioner of Patents and Trademarks

Margaret V. Turner

Attest



US005938087A

United States Patent [19][11] **Patent Number:** **5,938,087****Randall**[45] **Date of Patent:** **Aug. 17, 1999****[54] SPUPT MINIMIZING DISPENSING
STRUCTURE**[75] **Inventor:** **Jeffrey T. Randall**, Oconomowoc, Wis.[73] **Assignee:** **AptarGroup, Inc.**, Crystal Lake, Ill.[21] **Appl. No.:** **08/877,759**[22] **Filed:** **Jun. 17, 1997**[51] **Int. Cl.⁶** **B65D 47/40**[52] **U.S. Cl.** **222/547; 222/556; 222/568;**
222/571[58] **Field of Search** **222/547, 556,**
222/568, 571**[56] References Cited****U.S. PATENT DOCUMENTS**

3,091,373	5/1963	Kirschenbaum	222/547
3,117,701	1/1964	Stull	222/571
3,563,422	2/1971	Cruikshank	222/547
3,833,150	9/1974	Visser-Patings	222/571
3,980,211	9/1976	Owens	222/547
4,427,138	1/1984	Heinlein	222/546

4,583,668	4/1986	Maynard, Jr.	222/568
4,811,871	3/1989	Wass et al.	222/477
5,139,182	8/1992	Appla	222/547
5,141,138	8/1992	Odet et al.	222/547
5,219,100	6/1993	Beck et al.	222/556
5,320,260	6/1994	Song et al.	222/547
5,392,938	2/1995	Dubach	215/254
5,454,489	10/1995	Vesborg	222/547
5,497,906	3/1996	Dubach	222/23
5,531,363	7/1996	Gross et al.	222/547
5,782,388	7/1998	De Nervo	222/556

Primary Examiner—J. Casimer Jacyna**Attorney, Agent, or Firm—Rockey, Milnamow & Katz, Ltd.****[57] ABSTRACT**

A spurt-resistant spout for a dispensing structure includes (1) an internal tubular portion having a through bore connecting a dispensing orifice of the spout with the interior of the container, and (2) a surrounding wall portion surrounding the tubular portion. The tubular portion and the surrounding wall portion are sized and located so that little or no fluid is retained in and across the spout bore so as to prevent, or minimize, obstruction of the bore.

26 Claims, 2 Drawing Sheets.